City of Seattle - Volume 3: Stormwater Flow Control and Water Quality Treatment Technical Requirements Manual

Directors' Rule 2009-005 (SPU), 17-2009 (DPD)

Technical Information Report (TIR) Worksheet

DPD Plan tag here

	·
PART 1: PROJECT OWNER AND ENGINEER	PART 2: PROJECT LOCATION
Project Owner	Project Address:
Project Engineer:	Other Related Permit Numbers
Engineering Firm:	
Phone:	Approximate dollar cost to comply with GSI:
PART 3: TYPE OF PROJECT	PART 4: AREA SUMMARY
Single Family Residential – NOT APPLICABLE Use Standard Drainage Standard Plan, not this form	Area Cleared or Disturbed (includes "laydown, staging areas etc.)
Parcel Based	Total New plus Replaced Impervious Surface 1:
Trail or Sidewalk	Total New and/ or Replaced Pollution Generating Impervious
For joint projects complete separate TIRs for each portion of the project. Refer to SDOT submittal requirements for Street Improvement Permits	Surface: Total Protected Area Total Project Area
PART 5: ENVIRONMENTALLY CRITICAL AREAS Steep Slope Potential Slide Riparian Corrido Landfill Known Wildlife Landslide	
PART 6: DRAINAGE BASIN Listed Creek Basin: Blue Ridge Creek, Broadview Creek, Discovery Park Creek, Durham Creek, Frink Creek, Golden Gardens Creek, Kiwanis Ravine/Wolfe Creek, Licton Springs Creek, Madrona Park Creek, Mee- Kwa-Mooks Creek, Mount Baker Park Creek, Puget Creek, Riverview Creek, Schmitz Creek, Taylor Creek, or Washington Park Creek	PART 7: PROJECT POINT OF DISCHARGE Directly to Designated Receiving Waters Public Storm Drain Wetland Public Combined Sewer
Non- Listed Creek Basin Designated Receiving Water: Duwamish River, Puget Sound, Lake Washington, Lake Union, Elliott Bay, Portage Bay, Union Bay, the Lake Washington Ship Canal Combined Sewer Service Area Capacity Constrained	On-Site only (complete infiltration)

Revised: January 7, 2010

PART 8: SOILS	
Total Quantity Cut (export): Total Quantity Fill	
Total Quantity Compost Amended Soil (import):	
Date of PIT Test: (or assumed default 0.25 inch/hr)	
Geotechnical Engineer: Geotechnical Report Completed	
Soil Type Slopes:	
High Groundwater Table (Large project - within 3 feet, Small project – within 1 foot)	
Seeps / Springs Contaminated Soils Bedrock	
PART 9: DESIGN SUMMARY Flow Control: Green Stormwater Infrastructure to MEF (all Forested Pasture projects) (Attach GSI to MEF Calculator) Peak Peak Pasture Wetland Water Quality: Basic Enhanced (all MF, Commercial, and Industrial in creek basins) Oil Control (High-use/AADT) Phosphorous	
Source Control: Describe land use:	
Describe any structural controls:	
Attach Pre-sizing tables and/or Modeling Calculations with SPU HydroStats output data to the end of this document. For more information and to download SPU HydroStats, visit: http://www.seattle.gov/dpd/Codes/StormwaterCode/Modeling/default.asp PART 10 SIGNATURE OF PROFESSIONAL ENGINEER (REQUIRED FOR PROJECTS WITH 5,000 SF OR GREATER OF NEW PLUS REPLACED IMPERVIOUS SURFACE 1) I, or a civil engineer under my supervision, have visited the site. Actual site conditions as observed were incorporated into this worksheet and attached documents. To the best of my knowledge the information provided here is accurate. Signed /date:	
PART 11 SIGNATURE OF RESPONSIBLE PARTY: (ONLYAPPLICABLE FOR PROJECTS WITH LESS THAN 5,000 SF OF NEW PLUS REPLACED IMPERVIOUS SURFACE ¹ .) I have visited the site. Actual site conditions as observed were incorporated into this worksheet and attached documents. To the best of my knowledge the information provided here is accurate. Signed /date:	
¹ "Impervious Surface" means any surface exposed to rainwater from which most water runs off. Common impervious surfaces include, but are not limited to, roof tops, walkways, patios, driveways, formal planters, parking lots or storage areas, concrete or asphalt paving, permeable paving, gravel surfaces subjected to vehicular traffic, compact gravel, packed earthen materials, and oiled macadam or other surfaces which similarly impede the natural infiltration of stormwater.	

Revised: January 7, 2010